

**SPECIFICATIONS OF MARINE GAS OIL ARE AS UNDER:**

Characteristics	Test Method	Limit	DMA
Appearance	Visual		Clear and Bright, Free from sediments
Colour	ATDM 1500		2.0
Density at 15° C, kg/m <sup>3</sup>	ISO 4075 or ISO 12185	Min/max	Min 840, max 890
Viscosity at 40° C, mm <sup>2</sup> /s	ISO 3104	min	1.5
		max	6
Flash point, ° C	ISO 2719	min	60
Pour Point (upper), ° C	ISO 3016	max	
Winter quality		max	-6
Summer quality			0
Cloud Point, ° C	ISO 3015	max	To report
Sulphur, % (m/m)	ISO 8754	max	0.5
Cetane number	ISO 5165	min	40
Carbon residue, (micro), (10%b) % (m/m)	ISO 10370	max	0.3
Carbon residue, (micro), % (m/m)	ISO 10370	-	To report
Ash, % (m/m)	ISO 6245	max	0.01
Sediment, % (m/m)	ISO 3735	-	To report
Total existent sediment % (m/m)	ISO 10307-1	-	To report
Water, % (V/V)	ISO 3733	-	To report
Vanadium, mg/kg	ISO 14597	-	To report
Aluminum plus silicon, mg/kg	ISO 10478	-	To report