

SERVO MARINE 0530

GRADES AVAILABLE - SERVO MARINE 0530

DESCRIPTION

Servo Marine 0530 oil is new generation Marine crankcase engine oil developed to meet the system oil requirement of modern, slow speed, two stroke cross head engines used in Marine propulsion operating on high viscosity fuel oils with high sulphur content.

This oil exhibit better TBN retention, dispersancy characteristics and superior rust and corrosion protection.

APPLICATION

Servo Marine 0530 is recommended for use in Two stroke Cross Head Marine Propulsion Engines as system oil.

PERFORMANCE BENEFITS

- Provides maximum protection from rust and corrosion
- Provides higher level of TBN retention.
- Separates easily from water.
- Superior detergent action.
- Excellent defoamancy property.

MANUFACTURERS APPROVAL

- Approved by MAN B&W Diesel A/S as System Oil for Two Stroke Slow Speed Marine Propulsion Engine.
- Approved by Wartsila, Switzerland Ltd for use in all Sulzer make Two Stroke Slow Speed Marine Propulsion Engine.

CHARACTERISTICS

GRADE	SERVO MARINE 0530
SAE GRADE	30
Kin. Viscosity cSt @ 100°C	10.5 – 12.4
Viscosity Index, Min	90
Flash point (COC), °C Min.	220
Pour Point, °C Max.	(-) 6
Total Base No., mg KOH/g, Min	6

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Commercial & Lube Dept., Lanka IOC PLC, Level 20, West Tower, World Trade Center, Echelon Square, Colombo 01.

E-Mail: vsakthivel@lankaio.com OR lankaio.com