



SERVO MARINE 7050

GRADES AVAILABLE - SERVO MARINE 7050

DESCRIPTION

Servo Marine 7050 is high quality Diesel Engine Cylinder Lubricant developed to provide protection for Diesel Engine Cylinders using residual fuels.

These oils exhibit excellent resistance to deposit formation and corrosive wear in addition to emulsion formation.

APPLICATION

Servo Marine 7050 is recommended for use as Cylinder Lubricant in large crosshead diesel engines operating on residual fuels.

PERFORMANCE BENEFITS

- Excellent control of piston and cylinder liner wear.
- Provides maximum protection from adhesive and corrosive wear at the higher operating temperatures.
- Ensures outstanding Piston and Liner cleanliness.
- Extended component life.

CHARACTERISTICS

GRADE	SERVO MARINE 7050
SAE GRADE	50
Kin. Viscosity cSt @ 100°C	19.3 - 21.5
Kin. Viscosity cSt @ 40°C	191 (typ)
Sp Gravity, @ 15°C	0.897
Viscosity Index Min	95
Flash point (COC), °C Min.	230
Pour Point, °C Max.	(-) 6
Total Base No., mg KOH/g	70

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Commercial & Lube Dept., Lanka IOC PLC, Level 20, West Tower, World Trade Center, Echelon Square, Colombo 01.

E-Mail: vsakthivel@lankaio.com OR lankaio.com