

Product Data Sheet

Servo Futura NXT 10W30

Gasoline & Hybrid Engine Oil



Description

Servo Futura NXT 10W30 is high performance engine oil for all new generation Gasoline & Gasoline Hybrid passenger cars and SUVs with after treatment devices (ATDs). This oil is blended from synthesized base stock and high performance additives to provide highest Oxidation Stability and very low oil consumption.

Performance, Features and Benefits

- Provide minimum viscosity change and optimum film formation.
- Provides long service life and ultimate engine protection.
- Keeps the engine clean and provides outstanding wear protection at both low and high operating temperatures
- Provides better low temperature properties
- Provides good soot handling capacity of engine oil
- Compatible with after treatment devices
- Provide fuel economy

Application

Servo Futura NXT 10W30 is recommended as engine oil for all new generation passenger Cars & SUVs running on Gasoline/Hybrid. This oil is compatible with After Treatment devices, used to meet the Euro VI norms. This oil is also suitable for GDI Engines which may counter LSPI issues.

Approvals / Performance Standards / Recommendations

Servo Futura NXT 10W30 meets API SP and ILSAC GF6-A.

Typical Physical Characteristics

Properties	Method	10W-30
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	2.5
Flash Point COC, deg° C	ASTM D92	Min 200
Pour Point, deg° C	ASTM D97	Max -27
Kinetic viscosity at 100° C, cSt	ASTM D445	10.1 (Typical)
Kinetic viscosity at 40° C, cSt	ASTM D445	60.8 (Typical)
Viscosity Index	ASTM D2270	Min 140
HTHS @150 C, mPa.s	ASTM D4863	Min 2.9
Volatility, % wt loss	ASTM D5800	5.2 (Typical)
Low Temperature Cranking Viscosity at -25° C, cP	ASTM D5293	3880 (Typical)
Total base number, mgKOH/g	ASTM D2896	Min 6.3
Foam test; Tend/Stab, ml		
Seq. I		0/0
Seq. II	ASTM D892	20/0
Seq. III		0/0
Sulfated ash, % wt	ASTM D 874	0.7 (Typical)

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

07 JAN 2021

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,
Indian Oil Corporation Ltd.,
G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051

E-Mail: servotechserv@indianoil.in or
servots@indianoil.in | <https://cx.indianoil.in/>