

Product Data Sheet

Servo Pride ALT 15W-40



Description

Servo Pride ALT 15W-40 is premium commercial diesel engine oil. The oil is designed for the most severe performance requirements of new generation diesel engines for on and off highway operations. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations. It exhibits outstanding control on soot induced thickening and soot induced wear.

Performance, Features and Benefits

- Reduced engine scuffing and bore polishing.
- High engine cleanliness.
- Maximum protection from wear and deposits.
- Suitable for mixed fleet operation.
- Improved control of oil consumption.
- Easier cold starting.
- Excellent weather performance due to improved cold weather properties.

Application

Servo Pride ALT 15W-40 is recommended for new generation commercial diesel vehicles complying to Euro Stage II & III emission norms. It is suitable for use with high sulphur content diesel fuel.

Approvals / Performance Standards / Recommendations / Manufacturers Approval.

API CH-4, MB 228.5

Approval : Ashok Leyland Ltd, Chennai.

Typical Physical Characteristics

SAE GRADE	ALT 15W-40
Kin. Viscosity @ 100 °C, cSt	13.5 - 15.5
Viscosity Index, Min	135
Flash Point, COC, °C, Min	200
TBN mg KOH/gm	9.0 - 11.5
Pour Point, °C, Max	(-) 24

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

04 MAY 2021

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,
Indian Oil Corporation Ltd.,
G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051

E-Mail: servotechserv@indianoil.in or
servots@indianoil.in | <https://cx.indianoil.in/>