Product Data Sheet

Servo Futura NXT 0W-20

BS VI Compliant Gasoline Engine Oils

Description

Servo Futura NXT 0W-20 are high performance gasoline engine oil for all new generation Gasoline passenger cars and SUVs with after treatment devices (ATDs). These oils are blended from synthesized base stocks and high performance additives to provide highest Oxidation Stability and very low oil consumption. These oils are BS VI compliant.

Performance, Features and Benefits

- Provides minimum viscosity change and optimum film formation.
- Provides Long service life and ultimate engine protection.
- Keeps the engine clean and provides outstanding wear protection at both low and high operating temperatures.
- Provides better low temperature properties
- Provides good soot handling capacity of engine oil
- Compatible with after treatment devices.
- Provides fuel economy

Application

Servo Futura NXT 0W-20 are recommended as Engine oil for all new generation passenger Cars & SUVs running on petrol/ gasoline. These oils are compatible with After Treatment Devices, used to meet the BS VI norms. These oils are also suitable for GDI Engines which may counter LSPI issues.

Approvals / Performance Standards / Recommendations

Servo Futura NXT 0W-20 meets API SQ / ILSAC GF7

Typical Physical Characteristics

Properties	Method	0W-20
Appearance	Visual	Clear & Bright
Colour	ASTM D1500	2.0
Flash point COC, deg °C	ASTM D92	220
Pour Point, deg °C	ASTM D97	-42
Kinematic viscosity at 100°C, cSt	ASTM D445	8.05
Kinematic viscosity at 40°C, cSt	ASTM D445	41.03
Viscosity Index	ASTM D2270	173
HTHS @ 150 °C, mPa.s	ASTM D4863	2.66
Total base number, mg KOH/g	ASTM D2896	7.5
Foam test; Tend/Stab, ml Seq. I Seq. II Seq. III	ASTM D892	 10/0 40/0 10/0
Sulfated ash, % wt	ASTM D874	0.73

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at https://cx.indianoil.in/. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

07 JAN 2021

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:
Technical Services Department,
Indian Oil Corporation Ltd.,
G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051
E-Mail: servotechserv@indianoil.in or servots@indianoil.in | https://cx.indianoil.in/