

# Product Data Sheet

## Servo4T Zoom(10W-30/ 20W-40/20W-50)

Four-Stroke High Performance Engine Oil for 2/3 Wheeler



### Description

Servo 4T Zoom is high performance engine oil for 4-stroke 2 and 3 wheelers. This oil has high viscosity index which provides protection under wide operating temperature range.

### Performance, Features and Benefits

- Maximizes power output
- Superior performance in terms of oxidation stability
- Excellent wear protection at high temperatures and severe operating conditions
- Outstanding overall engine cleanliness
- Enhanced engine life
- Higher fuel efficiency
- Potential for oil drain interval up to 6000 kms.

### Application

Servo 4T Zoom is recommended for new generation 4-stroke motorcycles, scooters and auto rickshaws.

### Approvals/ Performance Standards/Recommendations

Servo 4T Zoom meets the performance requirement of API SL and JASO MA 2 (T903:2016).

Meets API SM specification of Valve Train Wear (VTW).

### Typical Characteristics

Properties	Method	Servo 4T Zoom	Servo 4T Zoom	Servo 4T Zoom
		10W-30	20W-40	20W-50
Flash point COC, °C,	ASTM D-92	228	230	232
Pour point, °C	ASTM D-97	-33	-30	-30
Kinematic viscosity at 100 °C, cSt	ASTM D-445	11.1	14.7	18.4
Viscosity Index	ASTM D-2270	142	128	136
Total base number, mg KOH/g	ASTM D-2896	6.15	6.20	6.10
Sulfated ash, % wt	ASTM D-874	0.77	0.79	0.78

### Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

23 JULY 2020

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,  
Indian Oil Corporation Ltd.,  
G-9, Ali Yavar Jung Marg, Bandra (E),  
Mumbai – 400051

E-Mail: [servotechserv@indianoil.in](mailto:servotechserv@indianoil.in) or  
[servots@indianoil.in](mailto:servots@indianoil.in) | <https://cx.indianoil.in/>